



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
31.03.1999 Bulletin 1999/13

(51) Int. Cl.⁶: **G02B 7/02**

(21) Application number: **98118385.8**

(22) Date of filing: **29.09.1998**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
 Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Ishihara, Keiichirou**
Ohta-ku, Tokyo (JP)

(74) Representative:
Pellmann, Hans-Bernd, Dipl.-Ing. et al
Patentanwaltsbüro
Tiedtke-Bühling-Kinne & Partner
Bavariaring 4
80336 München (DE)

(30) Priority: **30.09.1997 JP 282740/97**


(71) Applicant:
CANON KABUSHIKI KAISHA
Tokyo (JP)

(54) **Cylindrical lens and optical scanning device using the lens**

(57) A cylindrical lens is constructed by a plurality of optical elements (13a, 13b) for linearly imaging a laser beam. The cylindrical lens is fixed to an optical frame using an adhesive so as to prevent the adhesive from

entering a gap (34) between the optical elements (13a, 13b).

FIG. 1



Description

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The present invention relates to a cylindrical lens which is used in, e.g., an image forming apparatus, and linearly images a laser beam originating from a laser light source, and an optical scanning device which uses the cylindrical lens and images a laser beam deflected by a deflection means onto a surface to be scanned via an imaging lens.

Related Background Art

[0002] In a conventional optical scanning device used in an image forming apparatus such as a laser printer or the like, as shown in, e.g., Fig. 1, a laser unit 2 is fixed to a predetermined position of an optical frame 1. A laser beam L coming from the laser unit 2 is linearly focused by a cylindrical lens 3, is deflected by a polygonal mirror 4 which is rotated by the drive force of a drive motor 5, and forms a beam spot on a surface 8 to be scanned of a photosensitive body via imaging lenses 6 and 7.

[0003] As shown in Fig. 2, the cylindrical lens 3 has an integrated structure obtained by adhering a first lens 3a having a positive refractive power, and a second lens 3b having a negative refractive power, to each other. When the cylindrical lens 3 is fixed to the optical frame 1, an adhesive 9 is interposed between the optical frame 1 and cylindrical lens 3, the position of the cylindrical lens 3 is adjusted to form a desired spot shape on the surface 8 to be scanned, and the lens 3 is then fixed.

[0004] However, the cylindrical lens 3 is adjusted before the adhesive 9 is set. During the adjustment, the adhesive 9 may enter the effective portion from a gap 3c between the first and second lenses 3a and 3b. For this reason, in the conventional optical scanning device, the adhesive that has entered the effective portion of the cylindrical lens 3 intercepts, refracts, and scatters the laser beam, and the spot image on the surface 8 to be scanned may deform. When such optical scanning device is used in the image forming apparatus, the image quality deteriorates.

SUMMARY OF THE INVENTION

[0005] It is an object of the present invention to solve the above-mentioned problem, and to provide a cylindrical lens which can prevent an adhesive from entering the gap between optical elements, and an optical scanning device using the lens.

[0006] In order to achieve the above object, according to the present invention, a cylindrical lens which is comprised of a plurality of optical elements and linearly images a laser beam, comprises adhesive entrance

preventing means for preventing an adhesive used for fixing the optical elements to an optical frame from entering a gap between the optical elements.

[0007] Also, an optical scanning device according to the present invention comprises a laser light source for emitting a laser beam, a cylindrical lens which is comprised of a plurality of optical elements and linearly images a laser beam, deflection means for deflecting the laser beam coming from the cylindrical lens, an imaging lens for imaging the laser beam from the deflection means on a surface to be scanned, an optical frame for holding the cylindrical lens, and adhesive entrance preventing means for preventing an adhesive used for fixing the cylindrical lens to the optical frame from entering a gap between the optical elements.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008]

Fig. 1 is a view showing the arrangement of a conventional optical scanning device;

Fig. 2 is an enlarged view of a cylindrical lens portion;

Fig. 3 is a plan view showing an optical scanning device according to the first embodiment of the present invention;

Fig. 4 is a perspective view of a cylindrical lens;

Fig. 5 is a longitudinal sectional view of Fig. 4;

Fig. 6 is a perspective view of a second lens;

Fig. 7 is an explanatory view of a method of adjusting a first lens with respect to the first lens;

Fig. 8 is a sectional view of a cylindrical lens according to the second embodiment of the present invention; and

Fig. 9 is a perspective view of a second lens.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0009] The present invention will be described in detail hereinafter on the basis of its embodiments illustrated in Figs. 3 to 9.

[0010] Fig. 3 is a plan view of an optical scanning device according to the first embodiment of the present invention. A laser unit 12 for emitting a laser beam L is attached to a predetermined position of an optical frame 11. In the direction in which the laser beam L originating from the laser unit 12 travels, a cylindrical lens 13 having first and second lenses 13a and 13b, and a polygonal mirror 16 as a deflector supported by a drive motor 15 are placed in turn. The cylindrical lens 13 linearly images the laser beam L coming from the laser unit 12 on a deflection reflection surface of the polygonal mirror 16, which deflects the laser beam L coming from the cylindrical lens 13. In the direction in which the laser beam L deflected by the polygonal mirror 16 travels, imaging lenses 17 and 18, and a surface 19 to be

scanned, are placed. The members 11 to 18 are fixed to the optical frame 11, and the surface 19 to be scanned is a surface of a photosensitive body as a recording medium, which is rotatably placed outside the optical frame 11.

[0011] The first lens 13a of the cylindrical lens 13 consists of glass having a positive refractive power, and the second lens 13b consists of plastic having a negative refractive power. The cylindrical lens 13 is adjusted to be able to form a spot image with a desired shape on the surface 19 to be scanned, and is fixed to the optical frame 11 by an adhesive. The imaging lenses 17 and 18 have f- θ characteristics. Of these imaging lenses 17 and 18, for example, the imaging lens 18 is a plastic anamorphic lens having an aspheric shape. The cylindrical lens 13 is placed so that its imaging point is located at the object point of the imaging lenses 17 and 18, and has a temperature compensation function. With this function, even when the focal length of the imaging lens 18 has changed due to a change in temperature, the cylindrical lens 13 can prevent the spot image on the surface 19 to be scanned from deforming.

[0012] Fig. 4 is a perspective view of the cylindrical lens 13, Fig. 5 is a longitudinal sectional view of Fig. 4, and Fig. 6 is a perspective view of the second lens 13b. The second lens 13b has a box-shaped lens body 20. A concave surface portion 21 is formed on the lens body 20 on the joint side with the first lens 13a, and serves as an effective portion for effectively refracting the laser beam L. Around the concave surface portion 21, a contact reference surface 22a for regulating the spacing from the first lens 13a in the optical axis direction is formed. A fitting portion 23 for receiving the first lens 13a is integrally formed on the lens body 20 on the concave surface portion 21 side. When the first lens 13a is fitted into the fitting portion 23 and comes into contact with the contact reference surface 22a in the axial direction, and upper and lower contact reference surfaces 22b and 22c, the optical axes of the first and second lenses 13a and 13b substantially agree with each other.

[0013] The fitting portion 23 is constructed by a bottom plate 24 and side plates 25 and 26, and the reference surfaces 22a, 22b, and 22c upon fitting the first lens 13a into the fitting portion 23 are respectively formed on upper and lower recess portions and the bottom plate 24 of the fitting portion 23. The inner surfaces of the side plates 25 and 26 respectively serve as adhesive land portions 28 and 29 for holding an adhesive used for fixing the first lens 13a, and a small gap is formed between the first lens 13a and the concave surface portion 21 of the second lens 13b. Reference portions 30 to 33 used for precisely aligning the second lens 13b to the optical frame 11 are formed on the lower surfaces of the lens body 20 and side plates 25 and 26.

[0014] Upon assembling the first and second lenses 13a and 13b, as shown in the perspective view of Fig. 7, the first lens 13a is fitted into the fitting portion 23 by bringing it into contact with the contact reference sur-

faces 22a, 22b, and 22c from the space between the side plates 25 and 26 of the second lens 13b, so that the optical axes of the first and second lenses 13a and 13b precisely agree with each other. An ultraviolet setting adhesive is applied on the adhesive land portions 28 and 29, and is set by irradiating ultraviolet rays, thus integrating the first and second lenses 13a and 13b. Subsequently, a laser beam L' which is the same as the above-mentioned laser beam L is transmitted through the first and second lenses 13a and 13b to observe the imaging position of the laser beam L', and the position of the integrated cylindrical lens 13 is adjusted so that a line image is formed at a desired position on an ideal axis X.

[0015] Upon fixing the integrated cylindrical lens 13 to the optical frame 11, an adhesive 40 is interposed between the second lens 13b and optical frame 11, and is set after the position of the second lens 13b in the optical axis direction is adjusted.

[0016] In this optical scanning device, the laser beam L coming from the laser unit 12 is linearly focused by the cylindrical lens 13, is deflected by the polygonal mirror 16, and forms a beam spot on the surface 19 to be scanned by the imaging lenses 17 and 18. In this case, a change in imaging position of the imaging lenses 17 and 18 resulting from a temperature change is corrected by the cylindrical lens 13.

[0017] In the first embodiment, since the second lens 13b has the fitting portion 23 for receiving the first lens 13a, an adhesive can be prevented from entering a gap 34 between the first and second lenses 13a and 13b upon fixing the cylindrical lens 13 to the optical frame 11. Also, this fitting portion 23 can prevent the adhesive from entering the effective portion between the first and second lenses 13a and 13b. Furthermore, the fitting portion 23 prevents the gap between the first and second lenses 13a and 13b from being exposed. Hence, the laser beam can be prevented from being intercepted, refracted, scattered, and so forth by the adhesive, and a desired spot image can be formed on the surface 19 to be scanned. When the optical scanning device is used in an image forming apparatus, a high-quality image can be obtained.

[0018] Fig. 8 is a longitudinal sectional view of a cylindrical lens 13' according to the second embodiment of the present invention, and Fig. 9 is a perspective view of a second lens 13b. A partitioning plate 35 projects downward from the lower surface of a bottom plate 24 at the entrance of a fitting portion 23 of a second lens 13b' along the edge of the bottom plate 24. The height of the partitioning plate 35 is set to substantially reach a plane formed by reference portions 30 to 33, so that an adhesive used for adhesion with an optical frame 11 can be prevented from entering the fitting portion 23. The second embodiment can obtain the same effect as in the first embodiment, and can prevent the adhesive from entering the fitting portion 23 from the bottom plate 24 side more satisfactorily than the first embodiment.

[0019] Note that the method of adjusting the optical axis of the first lens 13 to that of the second lens 13b or 13b' is not limited to the above-mentioned method. For example, a method of imaging the laser beam L on the surface 19 to be scanned and checking its spot shape can also assure precise adjustment. The fitting portion 23 of the first embodiment or the partitioning plate 35 of the second embodiment is integrally formed, but may be fixed to the lens body 20 as an independent member.

[0020] To restate, in the optical scanning device of the present invention, the laser unit for emitting a laser beam, the cylindrical lens 13 for linearly imaging the laser beam L coming from the laser unit, the polygonal mirror for deflecting the laser beam coming from the cylindrical lens 13, and the imaging lenses for imaging the laser beam from the polygonal mirror on the surface to be scanned are placed in the optical frame. The cylindrical lens 13 comprises the first and second lenses 13a and 13b, and the second lens 13b is formed with the fitting portion 23 for receiving the first lens 13a. Upon fixing the cylindrical lens 13 to the optical frame using an adhesive, the fitting portion 23 can prevent the adhesive from entering the gap 34 between the first and second lenses 13a and 13b.

[0021] As described above, since a cylindrical lens and optical scanning device using the lens according to the present invention comprise adhesive entrance preventing means for preventing an adhesive from entering the gap between optical elements of the cylindrical lens, the laser beam can be prevented from being intercepted, refracted, scattered, and so on, and a spot image can be prevented from deforming. Also, when the optical scanning device is used in an image forming apparatus, a high-quality image can be obtained.

[0022] A cylindrical lens is constructed by a plurality of optical elements for linearly imaging a laser beam. The cylindrical lens is fixed to an optical frame using an adhesive so as to prevent the adhesive from entering a gap between the optical elements.

Claims

1. A cylindrical lens, which is constructed by a plurality of optical elements and linearly images a laser beam, comprising:

adhesive entrance preventing means for preventing an adhesive used for fixing said cylindrical lens to an optical frame from entering a gap between said optical elements.

2. A lens according to claim 1, wherein said plurality of optical elements include a first lens having a positive refractive power, and a second lens having a negative refractive power.

3. A lens according to claim 2, wherein said adhesive entrance preventing means prevents the adhesive

from entering an effective portion of said first and second lenses.

4. An optical scanning device comprising:

a laser light source for emitting a laser beam;
a cylindrical lens which is constructed by a plurality of optical elements and linearly images the laser beam emitted by said laser light source;
deflection means for deflecting the laser beam originating from said cylindrical lens;
an imaging lens for imaging the laser beam coming from said deflection means on a surface to be scanned;
an optical frame for holding said cylindrical lens; and
adhesive entrance preventing means for preventing an adhesive used for fixing said cylindrical lens to said optical frame from entering a gap between said optical elements.

5. A device according to claim 4, wherein said plurality of optical elements include a first lens having a positive refractive power, and a second lens having a negative refractive power.

6. A device according to claim 4, wherein said adhesive entrance preventing means prevents the adhesive from entering an effective portion of said cylindrical lens.

7. A device according to claim 4, wherein said plurality of optical elements include first and second lenses, and

said adhesive entrance preventing means is a cylindrical portion which is formed on said second lens and receives said first lens.

8. A device according to claim 7, wherein a downward plate member is formed on an edge of a bottom plate of said cylindrical portion.

9. A device according to claim 4, wherein said imaging lens comprises more than one optical elements, at least one of which is a plastic anamorphic lens, and

said cylindrical lens is placed with an imaging point thereof being located at an object point of said imaging lens.

10. An image forming apparatus comprising:

a laser light source for emitting a laser beam;
a cylindrical lens which is constructed by a plurality of optical elements and linearly images the laser beam emitted by said laser light

- source;
deflection means for deflecting the laser beam originating from said cylindrical lens;
a recording medium;
an imaging lens for imaging the laser beam coming from said deflection means on a surface of said recording medium;
an optical frame for holding said cylindrical lens; and
adhesive entrance preventing means for preventing an adhesive used for fixing said cylindrical lens to said optical frame from entering a gap between said optical elements.
11. An apparatus according to claim 10, wherein said plurality of optical elements include a first lens having a positive refractive power, and a second lens having a negative refractive power.
12. An apparatus according to claim 10, wherein said adhesive entrance preventing means prevents the adhesive from entering an effective portion of said cylindrical lens.
13. An apparatus according to claim 10, wherein said plurality of optical elements include first and second lenses, and

said adhesive entrance preventing means is a cylindrical portion which is formed on said second lens and receives said first lens.
14. An apparatus according to claim 13, wherein a downward plate member is formed on an edge of a bottom plate of said cylindrical portion.
15. An apparatus according to claim 10, wherein said imaging lens comprises more than one optical elements, at least one of which is a plastic anamorphic lens, and

said cylindrical lens is placed with an imaging point thereof being located at an object point of said imaging lens.
16. An optical system including a plurality of lenses, comprising:

a first lens; and
a second lens combined with said first lens, said second lens having a cylindrical portion for receiving said first lens, said cylindrical portion preventing a gap between said first and second lenses from being exposed.
17. A system according to claim 16, wherein said first lens has a positive refractive power, and said second lens has a negative refractive power.
18. A system according to claim 16, wherein said optical system is a cylindrical lens for linearly imaging a laser beam.
19. An optical device comprising:

an optical system including a plurality of optical elements;
an optical frame for holding said optical system;
an adhesive for fixing said optical system to said optical frame; and
adhesive entrance preventing means for preventing said adhesive from entering a gap between said optical elements.
20. A device according to claim 19, wherein said plurality of optical elements include a first lens having a positive refractive power, and a second lens having a negative refractive power.
21. A device according to claim 19, wherein said adhesive entrance preventing means prevents the adhesive from entering an effective portion of said first and second lenses.
22. A device according to claim 19, wherein said optical system is a cylindrical lens for linearly imaging a laser beam.
23. An optical scanning device comprising:

a light source unit;
a deflector for deflecting and scanning a light beam coming from said light source unit;
an optical system which is inserted in an optical path between said light source unit and said deflector and includes a plurality of optical elements;
an optical frame for holding said optical system;
an adhesive for fixing said optical system to said optical frame; and
adhesive entrance preventing means for preventing said adhesive from entering a gap between said optical elements.
24. A device according to claim 23, wherein said plurality of optical elements include a first lens having a positive refractive power, and a second lens having a negative refractive power.
25. A device according to claim 23, wherein said adhesive entrance preventing means prevents the adhesive from entering an effective portion of said first and second lenses.
26. A device according to claim 23, wherein said optical

system is a cylindrical lens for linearly imaging the light beam coming from said light source unit onto a deflection reflection surface of said deflector.

27. An image forming apparatus comprising: 5
- a light source unit;
 - a deflector for deflecting and scanning a light beam coming from said light source unit;
 - a recording medium; 10
 - an imaging lens for imaging the light beam deflected and scanned by said deflector on a surface of said recording medium;
 - an optical system which is inserted in an optical path between said light source unit and said deflector and includes a plurality of optical elements; 15
 - an optical frame for holding said optical system;
 - an adhesive for fixing said optical system to said optical frame; and 20
 - adhesive entrance preventing means for preventing said adhesive from entering a gap between said optical elements.
- 25
28. An apparatus according to claim 27, wherein said plurality of optical elements include a first lens having a positive refractive power, and a second lens having a negative refractive power. 30
29. An apparatus according to claim 27, wherein said adhesive entrance preventing means prevents the adhesive from entering an effective portion of said first and second lenses. 35
30. An apparatus according to claim 27, wherein said optical system is a cylindrical lens for linearly imaging the light beam coming from said light source unit onto a deflection reflection surface of said deflector. 40
- 45
- 50
- 55

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 11 8385

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	PATENT ABSTRACTS OF JAPAN vol. 097, no. 011, 28 November 1997 & JP 09 184997 A (CANON INC), 15 July 1997 * abstract *	1-30	G02B7/02
X	PATENT ABSTRACTS OF JAPAN vol. 098, no. 001, 30 January 1998 & JP 09 243947 A (CANON INC), 19 September 1997 * abstract *	1-8, 10-14, 16-30	
A	PATENT ABSTRACTS OF JAPAN vol. 097, no. 011, 28 November 1997 & JP 09 184996 A (CANON INC), 15 July 1997 * abstract *	1	
A	EP 0 493 805 A (CANON KK) 8 July 1992 * column 3, line 11 - line 53 * * figure 3 *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			G02B
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 21 December 1998	Examiner Luck, W
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 11 8385

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-12-1998

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0493805 A	08-07-1992	JP 2821513 B	05-11-1998
		JP 4237013 A	25-08-1992
		JP 4234721 A	24-08-1992
		DE 69127963 D	20-11-1997
		DE 69127963 T	05-03-1998
		KR 9408682 B	24-09-1994
		US 5581391 A	03-12-1996
		US 5377038 A	27-12-1994

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

"Aspects of Relevant Market Analysis--The Product Dimension," *27th Annual Practising Law Institute Advanced Antitrust Seminar: Mergers, Markets and Joint Ventures*, December 1987 (with H. P. Kitt).

"The Intertemporal Behavior of Economic Profits," *International Journal of Industrial Organization* 3 (1985) 379-400 (with R. Connolly).

"An Empirical Test of Managerial, Life Cycle, and Cost of Capital Models of Merger Activity," *Journal of Industrial Economics*, March 1984.

"The Factors Affecting the Probability of Being Acquired: Evidence for the United States," *Economic Journal*, June 1983, pp. 391-398.

"Micro Determinants of Conglomerate Mergers," *Industrial Organization, Anti-Trust and Public Policy*, Craven, Ed., Kluwer-Nijhoff Publishers: Boston, October 1982.

"Savings Billions in Winter Fuel Costs: Quick Return Investments in Oil Heat Systems" (with Paul London and Sueanne Pfifferling), Staff Research Paper No. 5, CONEG Policy Research Center, Washington, D. C., June 1979.

June 2002

Economist's Report in Connection with *Regency Oldsmobile, Inc. v. General Motors Corp., et al.*, April 1990.

Economist's Report in Connection with *Aristomenis Deligiannis et al. v. PepsiCo, Inc., et al.*, February 1990.

Economist's Report in Connection with *Wesco v. Alloy*, Case No. 84-C-10909, U.S. District Court, Northern District of Illinois.

Economist's Report in *AMCI v. Western Union*, Superior Court of New Jersey Law Division: Essex County, Docket No. L-45055-85E.

Economist's Report in *Monroe Systems for Business, Division of Litton Systems, Inc. v. SCI Systems, Inc.*, Case No. 84-2650-D, U.S. District Court, District of New Jersey.

The Economic Effects of New York State's Returnable Beverage Container Law (co-author).

Economist's Report on Economic Issues in *Microbyte Corporation v. New Jersey State Golf Association, Microbyte Corporation, t/a Microbyte Computer Systems Corp. v. New Jersey State Golf Association*, Civil Action No. 84-0949, U.S. District Court, District of New Jersey.

An Economic Analysis of the Likely Competitive Effects of the Acquisition of Stanley Drapery Hardware by Newell Companies, Inc., January 31, 1985.

PAPERS AND PUBLICATIONS

"The Bottom Line on the Persistence of Profits" *Antitrust Insights, A NERA Perspective*, May/June 2002.

"Evenhandedness in Arbitration: The Case of Major League Baseball," *Eastern Economic Journal*, April - June 1989 (with O. H. Erikson and J. W. Moser).

"Interfirm Relationships," *The Cutting Edge of Antitrust: Lessons from Deregulation*, June 1988 (with H. P. Kitt).

"The Economic Rationale for Contracts: A Theory and Some Implications," *Practising Law Institute: Distribution and Marketing*, January 1988 (with H. P. Kitt).

Economist's Report in Connection with *Braun Inc. and The Gillette Company v. Optiva Corporation*, February 1999.

Economist's Report in Connection with *Biofertec Ltd. v. Louisville Laboratories, Inc., et al.*, December 1998.

Economist's Report in Connection with *JTC Petroleum Company v. Koch Materials Company, et al.*, August 1998.

Economist's Report in Connection with *Shimano Inc. and Shimano American Corporation v. SRAM Corporation*, August 1997.

Economist's Report in Connection with *Up Against the Wall, Inc. et al. v. Ralph Wilson Plastics, et al.*, August 1997.

Economist's Report in Connection with *Mr. Mattress Limited Partnership v. Sealy Mattress Company*, March 1997.

Economist's Report in Connection with *DHL Corporation and Subsidiaries, et al. vs. Commissioner of Internal Revenue*, Docket Nos. 19570-95 and 26103-95, March 13, 1997.

Economist's Report in Connection with Federal Funding of the Corporation for Public Broadcasting, March 29, 1995.

Economist's Report in Connection with U.S. Department of Justice Civil Investigative Demand No. 11882, February 24, 1995.

Economist's Report in Connection with *Citizen's First Securities Litigation*, May 1994.

Economist's Report in Connection with *Nestle Holding, Inc. v. Commissioner of Internal Revenue*, Docket No. 21562-90, July 1994.

Economist's Rebuttal Report in Connection with *Nestle Holding, Inc. v. Commissioner of Internal Revenue*, Docket No. 21562-90," March 1994.

Affidavits in Opposition to Defendant's Motions for Partial Summary Judgment, *American Professional Testing Service, Inc. v. Harcourt Brace Jovanovich Legal and Professional Publications, Inc.*, January 1994.

Evaluation of Economic Issues in Connection with USPS Proposed Regulation, May 1991 (with P. A. Beutel).

Economist's Report in Connection with Furr's Inc., November 1990.

REPORTS

Expert Witness Report of Dr. Steven Schwartz in *Sony Electronics, Inc. et al. v. Soundview Technologies, Inc.*, United States District Court, District of Connecticut, Lead Docket No. 3:00-CV-00754 (JBA) U.S.D.C./New Haven, June 2002.

Expert Report of Steven Schwartz in *Greene, Tweed of Delaware, Inc. v. DuPont Dow Elastomers L.L.C. and E.I. DuPont De Nemours and Co., Inc.*, United States District Court for the Eastern District of Pennsylvania, Civil Action No. 00-CV-3058, March 2002.

Expert Report of Steven Schwartz in Connection with *Madison/OHI Liquidity Investors, LLC v. Omega Healthcare Investors, Inc.*, United States District Court, Eastern District of Michigan (Southern Division), Case No. 00-CV-72793-DT, December 2001.

Expert Report of Steven Schwartz *In the matter of CERTAIN PERSONAL WATERCRAFT AND COMPONENTS THEREOF*, United States International Trade Commission, Investigation No. 337-TA-452, September 4, 2001.

Economist's Report in Connection with *US Polo Association v. Meridian Hosiery Mills, Inc.*, American Arbitration Association, New York, New York, March 2001.

Expert Report of Steven Schwartz and Answering Expert Report of Steven Schwartz in Connection with *Dupont Pharmaceuticals Company and Dupont Contrast Imaging v. Molecular Biosystems, Inc., Mallinckrodt, Inc. and Nycomed Imaging AS*, January 2001 and February 2001.

Economist's Report in Connection with *Main Street Marketing of America, Inc. v. ICT Group, Inc.*, July 27, 2000.

Economist's Report in Connection with *Wells Fargo Bank, National Association v. U.S. Bank National Association*, September 16, 1999.

Supplemental Economist's Report in Connection with *The Iams Co. v. Kal Kan Foods*, May 26, 1999.

Economist's Report in Connection with *Watkins & Son Pet Supplies v. The Iams Company*, May 4, 1999.

Economist's Report for Mobil Corporation (with P. Beutel, B. Ray and J. Hall), April 15, 1999.

Economist's Report for Mediation in Connection with *Pitney Bowes v. United States Postal Service*, April 1999 and May 1999.

Deposition Testimony in *The Iams Company v. American Superior Feeds, et al.*, Civil Action No. C-3-90-14, U.S. District Court, Southern District of Ohio, Western Division (testimony given July 1992).

Trial and Deposition Testimony in *Trademark Research Corp. v. Maxwell Online, Inc.*, 90 Civ 5166(RJW), U.S. District Court, Southern District of New York (testimony given February, March and May, 1992).

Trial and Deposition Testimony in *Extrel FTMS, Inc. v. Bruker Instruments, Inc.*, Case 90-C-305-S, U.S. District Court, Western District of Wisconsin (testimony given August 1990 and September 1990).

Trial and Deposition Testimony in *Medcom Holding Co., v. Baxter Travenol Laboratories, Inc. and Medtrain, Inc.*, Civil Action No. 87C 9853, U.S. District Court, Northern District of Illinois, Eastern Division (testimony given September 1988, February 1990, October 1990, February 1991 and September 1993).

Trial Testimony in *Worlco Data Systems et al. v. Maxwell Communication Corp., et al.*, Civil Action No. 88-6597, U.S. District Court, Eastern District of Pennsylvania (testimony given February 1990).

Testimony before the New York State Moreland Act Commission to Investigate the Operation and Administration of the Returnable Container Act (testimony given October 11, 1989).

Trial and Deposition Testimony in *Revelations Antoine Ltee. v. K Mart Corp., et al.*, Case No. 88-0624, U. S. District Court, Eastern District of Virginia, Alexandria Division (testimony given July and September 1988).

Trial Testimony in *Data Systems of New Jersey, Inc., et al. v. Philips Business Systems, Inc.*, Case No. 78 Civ 6015 (CLB), U.S. District Court, Southern District of New York (testimony given March 1988).

Deposition Testimony in *Microbyte Corporation v. New Jersey State Golf Association*, U.S. District Court, District of New Jersey (testimony given October 1985 and February 1986).

Deposition Testimony in *Monroe Systems for Business, Division of Litton Business Systems, Inc. v. SCI Systems, Inc.*, Case No. 84-2650-D, U.S. District Court, District of New Jersey (testimony given September 1986).

Affidavit in Opposition to Plaintiff's Motion for Summary Judgment, *Henson Associates, Inc. v. Atari Games, Inc., et al.*, July 1985.